

What is claimed is:

1. A buckle comprising:

a female body formed with a flat housing and a male body having flexible insertion legs which are engaged with each other by insertion,

wherein a concave portion or a convex portion is provided at the center of butting portions on the plane of the female body and the male body when the female body engages with the male body, and the female body and the male body are thereby formed closely in contact.

2. The buckle according to claim 1, wherein horizontal straight portions are provided on both sides of a butting surface.

3. The buckle according to claim 1, wherein butting portions comprising straight portions and the concave portion or the convex portion are formed on both front and rear surfaces of the female body and the male body.

4. The buckle according to claim 1, wherein the butting portions comprising the straight portions and the concave portion or the convex portion are formed on one surface of the female body and the male body, and on the opposite surface, linear-form butting portions are formed.

5. The buckle according to claim 1, wherein the convex portion in the butting portions protrudes in a trapezoidal form where a front end is slightly narrowed, the concave portion

is concavely dented with the inlet expanded, and the straight portions and the convex portion or concave portion form the butting portions.

6. The buckle according to claim 1, wherein the convex portion in the butting portions protrudes arcuately, the concave portion curves in arcuately, and the straight portions and convex portion or concave portion form the butting portions.

7. The buckle according to claim 1, wherein the butting portion of the female body is formed by the straight portions and the concave portion and the butting portion of the male body is formed by the straight portions and the convex portion.

8. The buckle according to claim 1, wherein the butting portion of the female body is formed by the straight portions and the convex portion and the butting portion of the male body is formed by the straight portions and the concave portion.

9. The buckle according to claim 7, wherein the peripheral corners of straight portions on both sides and the convex portion at the center in the male body are notched to form a one level lower stepped portion, which is allowed to be fitted into the butting portion of the female body in a manner of overlapping.

10. The buckle according to claim 8, wherein the concave portion provided at the center of the male body is formed concavely up to a belt through hole, while the convex portion

of the female body is extended to the belt through hole.

11. The buckle according to claim 8, characterized in that the concave portion disposed at the center of the male body is formed concavely up to the belt through hole, while the convex portion of the upper plate of the female body is extended to a top surface of the belt through hole or a top surface or the top surface of a hooking member.